

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

21 1. (Currently Amended) A method of tucking a pair of opposing, refastenable side seams into a body portion of a pant-like garment, each refastenable side seam including at least one resilient component, the method comprising the steps of:

positioning the body portion of the pant-like garment between an upper conveyor having an upper vacuum zone and a lower conveyor having a lower vacuum zone, with the refastenable side seams in a fastened position;

holding apart a front region of the body portion from a back region of the body portion using opposing vacuum forces from the upper and lower vacuum zones;

pushing the refastenable side seams into the body portion a distance toward one another while the opposing vacuum forces are holding apart the front region of the body portion from the back region of the body portion, creating longitudinal folds in the garment along outer longitudinal edges of the upper and lower vacuum zones; and

compressing the garment with each of the at least one resilient components pushed into the body portion and in a flat conformation.

2. (Original) The method of Claim 1, wherein the upper vacuum zone and the lower vacuum zone each have a transverse width about equal to a desired folded transverse width of the body portion of the garment.

3. (Original) The method of Claim 1, further comprising the step of using a plurality of mechanical tucking blades to push the opposing side seams into the body portion toward one another.

4. (Original) The method of Claim 1, further comprising the step of using a pair of opposing mechanical tucking blades, each mechanical tucking blade positioned between the upper conveyor and one of the side seams, to push the opposing side seams into the body portion toward one another.

a 5. (Original) The method of Claim 1, further comprising the step of using a pair of opposing mechanical tucking blades, each mechanical tucking blade positioned between the lower conveyor and one of the side seams, to push the opposing side seams into the body portion toward one another.

6. (Original) The method of Claim 1, further comprising the step of using a pair of opposing mechanical tucking blades to push the opposing side seams into the body portion toward one another, with one of the mechanical tucking blades positioned between the upper conveyor and one of the side seams, and one of the mechanical tucking blades positioned between the lower conveyor and one of the side seams.

7. (Original) The method of Claim 1, further comprising the step of directing a pair of opposing air bars toward the opposing side seams prior to pushing the opposing side seams into the body portion toward one another.

8. (Original) The method of Claim 1, further comprising the step of reducing a distance between the upper conveyor and the lower conveyor subsequent to pushing the opposing side seams into the body portion toward one another.

9. (Original) The method of Claim 1, further comprising the step of reducing a distance between the upper conveyor and the lower conveyor while pushing the opposing side seams into the body portion toward one another.

10. (Original) The method of Claim 1, further comprising the step of inserting the garment between two consecutive stacker finger units subsequent to pushing the opposing side seams into the body portion toward one another.

11. (Original) The method of Claim 1, wherein the pant-like garment comprises a training pant.

a 12. (Original) The method of Claim 1, wherein the pant-like garment comprises a swim pant.

13. (Currently Amended) A method of tucking a pair of opposing, refastenable side seams into a body portion of a pant-like garment, each refastenable side seam including at least one resilient component, the method comprising the steps of:

positioning the body portion of the pant-like garment on a conveyor having a vacuum zone, with the refastenable side seams in a fastened position;

holding the body portion on the conveyor using vacuum force from the vacuum zone;

pushing the refastenable side seams into the body portion a distance toward one another while the vacuum force is holding the body portion on the conveyor, creating longitudinal folds in the garment along outer longitudinal edges of the vacuum zone; and

compressing the garment with each of the at least one resilient components pushed into the body portion and in a flat conformation.

14. (Original) The method of Claim 13, wherein the vacuum zone has a vacuum in a range of between about 1 inch of water and about 100 inches of water.

15. (Original) The method of Claim 13, wherein the vacuum zone has a vacuum in a range of between about 2 inches of water and about 50 inches of water.

16. (Original) The method of Claim 13, wherein the vacuum zone has a vacuum in a range of between about 3 inches of water and about 35 inches of water.

a 17. (Original) The method of Claim 13, wherein the vacuum zone has a transverse width about equal to a desired folded transverse width of the body portion of the garment.

18. (Original) The method of Claim 13, further comprising the step of using a plurality of mechanical tucking blades to push the opposing side seams into the body portion toward one another.

19. (Original) The method of Claim 18, further comprising the step of using the mechanical tucking blades to control the distance the refastenable side seams are pushed into the body portion toward one another.

20. (Original) The method of Claim 13, further comprising the step of using vacuum dead plates to control the distance the refastenable side seams are pushed into the body portion toward one another.

21. (Original) The method of Claim 13, further comprising the step of using a pair of opposing mechanical tucking blades, each mechanical tucking blade positioned between the conveyor and one of the side seams, to push the opposing side seams into the body portion toward one another.

22. (Original) The method of Claim 13, further comprising the step of using a pair of opposing mechanical tucking blades to push the opposing side seams into the body portion toward one another, with each of the side seams positioned between one of the mechanical tucking blades and the conveyor.

23. (Original) The method of Claim 13, further comprising the step of using a pair of opposing mechanical tucking blades to push the opposing side seams into the body portion toward one another, with one of the mechanical tucking blades positioned between the conveyor and one of the side seams, and one of the side seams positioned between one of the mechanical tucking blades and the conveyor.

24. (Original) The method of Claim 13, further comprising the step of inserting the garment between two consecutive stacker finger units subsequent to pushing the opposing side seams into the body portion toward one another.

Claims 25-37 (Canceled)
